

Safety Data Sheet

MR 3

STABOND

SDS Revision: Version 1.3
SDS Revision Date: 12/4/2018

1. Identification

1.1. Product identifier

Product Identity MR 3

Alternate Names MR 3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name STABOND CORPORATION
1722 W. 139th Street, GARDENA CA. 90249

Customer Service: STABOND CORPORATION (310) 380-6168 Mon. to Fri. 07:00 – 15:30 PT

Emergency Contact: CHEMTREC (800) 424-9300 24-hour

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Liq. 2;H225	Highly Flammable liquid and vapor.
Skin Irrit. 2;H315	Causes skin irritation.
Repr. 2;H361F	Suspected of damaging fertility.
STOT RE 2;H373	May cause damage to organs through prolonged or repeated exposure. Specific Target Organs: (Not Available)
Aquatic Chronic 2;H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

[Prevention]:

- P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
 P235 Keep cool.
 P240 Ground / bond container and receiving equipment.
 P241 Use explosion-proof electrical / ventilating / light / equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe mist / vapors / spray.
 P262 Do not get in eyes, on skin, or on clothing.
 P264 Wash thoroughly after handling.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection / face protection.

[Response]:

- P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.
 P302+352 IF ON SKIN: Wash with plenty of soap and water.
 P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
 P308+313 IF exposed or concerned: Get medical advice / attention.
 P314 Get Medical advice / attention if you feel unwell.
 P321 Specific treatment (see information on this label).
 P331 Do NOT induce vomiting.
 P362 Take off contaminated clothing and wash before reuse.
 P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.
 P391 Collect spillage.

[Storage]:

- P403+233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.

[Disposal]:

- P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Solvent naphtha (petroleum), light aliphatic CAS Number: 0064742-89-8	25 - 50	Asp. Tox. 1;H304	[1]
Heptane CAS Number: 0000142-82-5	10 - 25	Flam. Liq. 2;H225 Asp. Tox. 1;H304 Skin Irrit. 2;H315	[1][2]

		STOT SE 3;H336 Aquatic Acute 1;H400 Aquatic Chronic 1;H410	
Hexane CAS Number: 0000110-54-3	10 - 25	Flam. Liq. 2;H225 Repr. 2;H361f Asp. Tox. 1;H304 STOT RE 2;H373 Skin Irrit. 2;H315 STOT SE 3;H336 Aquatic Chronic 2;H411	[1][2]
Aliphatic Hydrocarbon CAS Number: 0064742-49-0	10 - 25	Asp. Tox. 1;H304	[1]
Hydrocarbon waxes (petroleum), clay-treated microcryst. CAS Number: 0064742-42-3	1.0 - 10	Not Classified	[1]
Cyclohexane CAS Number: 0000110-82-7	1.0 - 10	Flam. Liq. 2;H225 Asp. Tox. 1;H304 Skin Irrit. 2;H315 STOT SE 3;H336 Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:
May cause irritation of upper respiratory tract. Excessive exposure may cause anesthetic or narcotic effects (headache, dizziness, drowsiness etc.)

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:
SKIN-Prolonged or repeated exposure may result in drying of the skin which can cause skin irritation or dermatitis.
EYES-Liquid or high vapor concentrations can be severely irritating to the eyes.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:
May be irritating. Persons with pre-existing skin disorders may be more susceptible to the effects of this material.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Moderate CNS depression may be shown by giddiness, headache, dizziness and nausea. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs, which can cause severe lung damage. Aspiration pneumonitis may be evidenced by coughing and cyanosis.

HEALTH HAZARDS (ACUTE AND CHRONIC):

Eye: May cause irritation with tearing.

Skin: May cause skin irritation and dermatitis.

Ingestion: May cause irritation and corrosion on the mouth and stomach tissue.

Inhalation: May cause irritation to upper respiratory tract and at higher concentrations narcosis or CNS depression.

CARCINOGENICITY: NTP? NO, IARC MONOGRAPHS? NO, OSHA REGULATED? NO

This product contains chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Skin contact may aggravate an existing dermatitis. Preexisting eye and respiratory disorders may be aggravated.

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Skin

Causes skin irritation.

5. Fire-fighting measures

5.1. Extinguishing media

Dry chemical, foam, carbon dioxide and water fog.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Carbon dioxide, carbon monoxide and hydrochloric acid.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

5.3. Advice for fire-fighters

Volatile solvent constituent can readily form explosive or flammable mixtures in air. Vapors can flow along surfaces to distant ignition sources and flash back.

Wear self-contained breathing apparatus and full protective clothing.

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Handle as a flammable liquid. Remove all ignition sources. Soak up wet material on a non-combustible absorbent and place in a closed metal container.

7. Handling and storage

7.1. Precautions for safe handling

Ground and bond metal containers when dispensing. No smoking in areas of use or storage. Use only non-sparking tools near wet adhesive or solvent vapors. Solvent vapor is much heavier than air and can collect in dangerous concentrations in floor drains or low areas.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Strong oxidizing agents and acids.

Store in cool, well ventilated area away from any ignition sources and strong oxidizing agents. Keep containers tightly closed when not in use. Do not transfer to plastic containers.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters**Exposure**

CAS No.	Ingredient	Source	Value
0000110-54-3	Hexane	OSHA	TWA 500 ppm (1800 mg/m ³)
		ACGIH	TWA: 20 ppmSkin
		NIOSH	TWA 50 ppm (180 mg/m ³)

		Supplier	No Established Limit
0000110-82-7	Cyclohexane	OSHA	TWA 300 ppm (1050 mg/m3)
		ACGIH	TWA: 100 ppm
		NIOSH	TWA 300 ppm (1050 mg/m3)
		Supplier	No Established Limit
0000142-82-5	Heptane	OSHA	TWA 500 ppm (2000 mg/m3)
		ACGIH	TWA: 400 ppm STEL: 500 ppm
		NIOSH	TWA 85 ppm (350 mg/m3) C 440 ppm (1800 mg/m3) [15-minute]
		Supplier	No Established Limit
0064742-42-3	Hydrocarbon waxes (petroleum), clay-treated microcryst.	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-49-0	Aliphatic Hydrocarbon	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-89-8	Solvent naphtha (petroleum), light aliphatic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000110-54-3	Hexane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000110-82-7	Cyclohexane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000142-82-5	Heptane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-42-3	Hydrocarbon waxes (petroleum), clay-treated microcryst.	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-49-0	Aliphatic Hydrocarbon	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-89-8	Solvent naphtha (petroleum), light aliphatic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory	Atmospheric levels should be maintained below the exposure guideline. Use an approved, full-face, supplied air respirator or a NIOSH approved positive pressure, self-contained breathing apparatus if these levels are exceeded.
Eyes	Use safety glasses with side shields or chemical goggles. If exposure causes eye discomfort, use a full-face respirator.
Skin	Use Neoprene, vinyl or nitrile rubber gloves.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Eye wash fountain or bottles. Solvent insoluble barrier hand cream. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Low Viscosity Liquid
Odor	Mild, Non-Residual Odor
Odor threshold	Not Measured
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	148 to 209 Deg F
Flash Point	-10 Deg F (TCC)
Evaporation rate (Ether = 1)	Slower than Ether
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1.0% Upper Explosive Limit: 8.4%
Vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	0.7
Solubility in Water	Nil
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
Coating V.O.C.	5.54 lb/gl (664 grams/liter)
Material V.O.C.	5.54 lb/gl (664 grams/liter)

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Excessive heat and open flame.

10.5. Incompatible materials

Strong oxidizing agents and acids.

10.6. Hazardous decomposition products

Carbon dioxide, carbon monoxide and hydrochloric acid.

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Solvent naphtha (petroleum), light aliphatic - (64742-89-8)	5,000.00, Mouse - Category: 5	3,000.00, Rabbit - Category: 5	No data available	No data available	No data available
Heptane - (142-82-5)	17,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	103.00, Rat - Category: NA	No data available	No data available
Hexane - (110-54-3)	25,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	No data available	No data available	48,000.00, Rat - Category: NA
Aliphatic Hydrocarbon - (64742-49-0)	5,000.00, Rat - Category: 5	3,160.00, Rabbit - Category: 5	No data available	No data available	No data available
Hydrocarbon waxes (petroleum), clay-treated microcryst. - (64742-42-3)	No data available	No data available	No data available	No data available	No data available
Cyclohexane - (110-82-7)	12,705.00, Rat - Category: NA	2,000.00, Rabbit - Category: 4	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	2	Suspected of damaging fertility.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Solvent naphtha (petroleum), light aliphatic - (64742-89-8)	Not Available	Not Available	4,700.00 (72 hr), Selenastrum capricornutum
Heptane - (142-82-5)	375.00, Oreochromis mossambicus	50.00, Daphnia magna	Not Available
Hexane - (110-54-3)	2.50, Pimephales promelas	3,878.00, Daphnia magna	Not Available
Aliphatic Hydrocarbon - (64742-49-0)	Not Available	2.60, Chaetogammarus marinus	Not Available
Hydrocarbon waxes (petroleum), clay-treated microcryst. - (64742-42-3)	Not Available	Not Available	Not Available
Cyclohexane - (110-82-7)	8.20, Morone saxatilis	3.78, Daphnia magna	500.00 (72 hr), Scenedesmus subspicatus

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations**13.1. Waste treatment methods**

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1993	UN1993	UN1993
14.2. UN proper shipping name	UN1993, Flammable liquids, n.o.s., (contains Hexane), 3, III	Flammable liquids, n.o.s., (contains Hexane)	Flammable liquids, n.o.s., (contains Hexane)
14.3. Transport hazard class(es)	DOT Hazard Class: 3 DOT Label: 3	IMDG: 3 Sub Class: Not Applicable	Air Class: 3
14.4. Packing group	II	II	II
14.5. Environmental hazards			
IMDG	Marine Pollutant: Yes (Solvent naphtha (petroleum), light aliphatic)		
14.6. Special precautions for user	No further information		

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
WHMIS Classification	B2 D2A
US EPA Tier II Hazards	Fire: Yes Sudden Release of Pressure: No Reactive: No Immediate (Acute): Yes Delayed (Chronic): Yes

EPCRA 311/312 Chemicals and RQs (lbs):

Cyclohexane (1,000.00)

Hexane (5,000.00)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Cyclohexane

Hexane

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

Hexane

New Jersey RTK Substances (>1%):

Cyclohexane

Heptane

Hexane

Pennsylvania RTK Substances (>1%):

Cyclohexane

Heptane

Hexane

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

INTENTIONAL MISUSE BY DELIBERATE INHALATION OF TOLUENE HAS BEEN ASSOCIATED WITH LIVER, KIDNEY, AND BRAIN DAMAGE IN HUMANS. OVEREXPOSURE TO TOLUENE HAS BEEN FOUND TO CAUSE LIVER, KIDNEY, NASAL, AND BRAIN DAMAGE IN LABORATORY ANIMALS. REPEATED OVEREXPOSURE TO HIGH VAPOR CONCENTRATIONS (1000ppm) OF N-HEXANE CAN CAUSE IRREVERSIBLE NERVE DAMAGE. THIS NEUROTOXICITY CAN BE ENHANCED BY THE PRESENCE OF METHYL ETHYL KETONE.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness and dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

SDS Revision History

Version 1.1	Initial SDS issued	2/5/2015
Version 1.2	Section 1.3 Change to Emergency Tele. Number	6/17/2015
Version 1.3	Section 1.3 Update to Emergency Tele. Number, Section 15 Hexane added to Prop 65 List	12/4/2018

ALL INFORMATION IS BASED UPON DATA FROM MFG'S AND/OR TECHNICAL SOURCE, & IS BELIEVED TO BE ACCURATE. CONDITIONS OF USE ARE BEYOND OUR CONTROL & THEREFORE USERS ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN CONDITIONS TO DETERMINE SUITABILITY FOR THEIR PURPOSE, & THEY ASSUME ALL RISKS OF USE, HANDLING, & DISPOSAL, OR FROM USE OF INFORMATION CONTAINED HEREIN. THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT RELATE TO ITS USE IN COMBINATION WITH OTHER MATERIAL OR IN ANY OTHER PROCESS.

End of Document