

Safety Data Sheet  
NS 230TP SCH



SDS Revision: Version 2.1  
SDS Revision Date: 06/28/2022

1. Identification

1.1. Product identifier

Product Identity NS 230TP SCH  
Alternate Names NS 230TP SCH - Foam Additive

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name STABOND CORPORATION  
1722 W. 139th Street, GARDENA CA. 90249

Emergency

24 hour Emergency Telephone No. Chemtrec CCN 20994  
24 hour emergency phone # 800 424 9300

Customer Service: STABOND CORPORATION 310 380 6168

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Liq. 2;H225	Highly Flammable liquid and vapor.
Skin Irrit. 2;H315	Causes skin irritation.
Eye Dam. 2A;H319	Causes serious eye irritation.
Repr. 1A;H360Fd	May damage fertility. Suspected of damaging the unborn child.
STOT SE 3;H336	May cause drowsiness or dizziness.
STOT RE 2;H373	May cause damage to organs through prolonged or repeated exposure. Specific Target Organs: (Not Available)
Aquatic Acute 2;H401	Toxic to aquatic life.
Aquatic Chronic 2;H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements



Danger

H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness and dizziness.

H360Fd May damage fertility. Suspected of damaging the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H401 Toxic to aquatic life.  
H411 Toxic to aquatic life with long lasting effects.

**[Prevention]**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.  
P233 Keep container tightly closed.  
P240 Ground, bond container and receiving equipment.  
P241 Use explosion-proof electrical, ventilating, light, equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust, fume, gas, mist, vapors, spray.  
P264 Wash thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves, eye protection, face protection.

**[Response]**

P302+352 IF ON SKIN: Wash with plenty of soap and water.  
P303+361+353 IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.  
P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.  
P308+313 IF exposed or concerned: Get medical advice or attention.  
P312 Call a POISON CENTER, doctor or physician if you feel unwell.  
P332+313 IF SKIN IRRITATION OCCURS: Get medical advice or attention.  
P337+313 If eye irritation persists: Get medical advice or attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.  
P391 Collect spillage.

**[Storage]**

P403+233 Store in a well ventilated place. Keep container tightly closed.  
P403+235 Store in a well ventilated place. Keep cool.  
P405 Store locked up.

**[Disposal]**

P501 Dispose of contents or container in accordance with local and national regulations.

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Hexane CAS Number: 0000110-54-3	25 - 50	Flam. Liq. 2;H225 Repr. 2;H361f Asp. Tox. 1;H304 STOT RE 2;H373 > 5% Skin Irrit. 2;H315 STOT SE 3;H336 Aquatic Chronic 2;H411	----
Acetone CAS Number: 0000067-64-1	25 - 50	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	----
Petroleum Hydrocarbon Resin C-5 CAS Number: Proprietary	5 - 10	Not Classified	----
Styrene-Butadiene polymer CAS Number: 0009003-55-8	5 - 10	Not Classified	----
Rosin, maleated, polymer with glycerol CAS Number: 0068038-41-5	5 - 10	Not Classified	----
Hydrocarbon Resin CAS Number: 0068478-07-9	5 - 10	Not Classified	----
Naphtha (petroleum), light steam-cracked arom., polymer with light steam-cracked arom. petroleum naphtha piperylene conc CAS Number: 0068527-25-3	5 - 10	Not Classified	----
2,2'-Methylenebis(4-methyl-6-tert-butylphenol) CAS Number: 0000119-47-1	1 - 5	Repr. 1A;H360Fd	----

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

\*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

### Section 4. First aid measures

#### 4.1. Description of first aid measures

<b>General</b>	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
<b>Eyes</b>	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
<b>Skin</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
<b>Ingestion</b>	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Overview**

Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. Check section 2.2 (GHS Label Elements) for further details.

**Inhalation**

May cause drowsiness or dizziness.

**Eyes**

Causes serious eye irritation.

**Skin**

Causes skin irritation.

### Section 5. Fire-fighting measures

#### 5.1. Extinguishing media

Dry chemical, foam, carbon dioxide and water fog.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Burning may produce fumes of hydrogen bromide. Chemical decomposition will produce hydrogen bromide.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Keep container tightly closed.

Ground, bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust, fume, gas, mist, vapors, spray.

#### 5.3. Advice for fire-fighters

High vapor concentrations (2-18% by volume) in air, exposed to high intensity spark or flame, can flash in confined or poorly ventilated areas. Vapors can flow along surfaces to distant ignition sources and flash back.

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water ways.

**ERG Guide No.** 128

## Section 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapor levels are below the Lower Explosive Limit before re-entering.

### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### 6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8. Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

## Section 7. Handling and storage

### 7.1. Precautions for safe handling

Ground and bond metal containers when dispensing. Not smoking in areas of use or storage. Use only non-sparking tools near wet adhesive or solvent vapors. Solvent vapor is much heavier than air and can collect in dangerous concentrations in floor drains or low areas.

Store in cool, well ventilated area away from any ignition sources and strong oxidizing agents. Keep containers tightly closed when not in use. Do not transfer to plastic containers.

Ground and bond metal containers when dispensing. No smoking in areas of use or storage. Use only non-sparking tools near wet adhesive or solvent vapors. Solvent vapor is much heavier than air and can collect in dangerous concentrations in floor drains or low areas.

Check section 2.2 (GHS Label Elements) for further details. - [Prevention]

### 7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials: Aluminum, caustic soda, caustic potash or oxidizing materials.

Check section 2.2 (GHS Label Elements) for further details. - [Storage]

### 7.3. Specific end use(s)

No data available.

## Section 8. Exposure controls / personal protection

### 8.1. Control parameters

CAS No.	Ingredient	Exposure	
		Source	Value
0000067-64-1	Acetone	OSHA	TWA 1000 ppm (2400 mg/m <sup>3</sup> ) STEL 2400 mg/m <sup>3</sup>
		ACGIH	TWA: 500 ppm STEL: 750 ppm
		NIOSH	250 ppm (590 mg/m <sup>3</sup> ) TWA
0000110-54-3	Hexane	OSHA	TWA 500 ppm (1800 mg/m <sup>3</sup> )

		ACGIH	TWA: 20 ppm
		NIOSH	TWA 50 ppm (180 mg/m <sup>3</sup> )
0000119-47-1	2,2'-Methylenebis(4-methyl-6-tert-butylphenol)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0009003-55-8	Styrene-Butadiene polymer	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0068038-41-5	Rosin, maleated, polymer with glycerol	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0068478-07-9	Hydrocarbon Resin	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0068527-25-3	Naphtha (petroleum), light steam-cracked arom., polymer with light steam-cracked arom. petroleum naphtha piperylene conc	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
Proprietary	Petroleum Hydrocarbon Resin C-5	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

**8.2. Exposure controls**

**Respiratory**

Atmospheric levels should be maintained below the exposure guideline. For normal use wear an NIOSH/MSHA approved air purifying, organic vapor cartridge respirator. For higher levels of exposure use an NIOSH/MSHA approved, full-face supplied air respirator or an approved positive pressure self-contained breathing apparatus.

**Eyes**

Safety glasses with side shields/goggles are recommended. Do not wear contact lenses.

**Skin**

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact. Nitrile, butyl or polyvinyl alcohol gloves.

**Engineering Controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

**Other Work Practices**

Eye wash fountain or bottles. Solvent insoluble barrier hand cream. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Check section 2.2 (GHS Label Elements) for further details.

## Section 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Color: Pink    Physical State: Liquid
<b>Odor</b>	Solvent
<b>Odor threshold</b>	Not determined
<b>pH</b>	Not Measured
<b>Melting point / freezing point</b>	Not Measured
<b>Initial boiling point and boiling range</b>	Not Measured
<b>Flash Point</b>	-25.99 °C
<b>Evaporation rate (Ether = 1)</b>	Not Measured
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> Not Measured <b>Upper Explosive Limit:</b> Not Measured
<b>Vapor pressure (Pa)</b>	Not Measured
<b>Vapor Density</b>	Not Measured
<b>Relative Density</b>	Not Measured
<b>Solubility in Water</b>	Insoluble
<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured
<b>Auto-ignition temperature</b>	Not Measured
<b>Decomposition temperature</b>	Not Measured
<b>Viscosity (cSt)</b>	Not Measured
<b>VOC Content</b>	Coating VOC 444 grams/liter 318 grams/liter
<b>Density</b>	0.79 g/cm <sup>3</sup>

### 9.2. Other information

No other relevant information.

## Section 10. Stability and reactivity

### 10.1. Reactivity

Hazardous Polymerization will not occur.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Gross water contamination can cause hydrolysis producing hydrogen bromide. Keep away from all ignition sources and heat.

### 10.5. Incompatible materials

Aluminum, caustic soda, caustic potash or oxidizing materials.

### 10.6. Hazardous decomposition products

Burning may produce fumes of hydrogen bromide. Chemical decomposition will produce hydrogen bromide.

**Section 11. Toxicological information**

**Acute toxicity**

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Hexane - (110-54-3)	25,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	No data available	No data available	48,000.00, Rat - Category: NA
Acetone - (67-64-1)	5,800.00, Rat - Category: NA	7,426.00, Rabbit - Category: NA	76.00, Rat - Category: NA	50.10, Rat - Category: NA	No data available
Petroleum Hydrocarbon Resin C-5 - (Proprietary)	No data available	No data available	No data available	No data available	No data available
Styrene-Butadiene polymer - (9003-55-8)	No data available	No data available	No data available	No data available	No data available
Rosin, maleated, polymer with glycerol - (68038-41-5)	No data available	No data available	No data available	No data available	No data available
Hydrocarbon Resin - (68478-07-9)	No data available	No data available	No data available	No data available	No data available
Naphtha (petroleum), light steam-cracked arom., polymer with light steam-cracked arom. petroleum naphtha piperylene conc - (68527-25-3)	No data available	No data available	No data available	No data available	No data available
2,2'-Methylenebis(4-methyl-6-tert-butylphenol) - (119-47-1)	> 5,000.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available	No data available	No data available

**Carcinogen Data**

CAS No.	Ingredient	Source	Value
0000067-64-1	Acetone	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	A4
0000110-54-3	Hexane	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0000119-47-1	2,2'-Methylenebis(4-methyl-6-tert-butylphenol)	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;



		ACGIH	No Established Limit
0009003-55-8	Styrene-Butadiene polymer	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
		ACGIH	No Established Limit
0068038-41-5	Rosin, maleated, polymer with glycerol	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0068478-07-9	Hydrocarbon Resin	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0068527-25-3	Naphtha (petroleum), light steam-cracked arom., polymer with light steam-cracked arom. petroleum naphtha piperylene conc	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
Proprietary	Petroleum Hydrocarbon Resin C-5	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2A	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	1A	May damage fertility. Suspected of damaging the unborn child.
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	---	Not Applicable

## Section 12. Ecological information

### 12.1. Toxicity

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Hexane - (110-54-3)	12.51, Oncorhynchus mykiss	21.85, Daphnia magna	9.285 (72 hr), Pseudokirchneriella subcapitata
Acetone - (67-64-1)	8,120.00, Pimephales promelas	8,800.00, Daphnia pulex	7,000.00 (96 hr), Pseudokirchneriella subcapitata
Petroleum Hydrocarbon Resin C-5 - (Proprietary)	Not Available	Not Available	Not Available
Styrene-Butadiene polymer - (9003-55-8)	Not Available	Not Available	Not Available
Rosin, maleated, polymer with glycerol - (68038-41-5)	Not Available	Not Available	Not Available
Hydrocarbon Resin - (68478-07-9)	Not Available	Not Available	Not Available
Naphtha (petroleum), light steam-cracked arom., polymer with light steam-cracked arom. petroleum naphtha piperylene conc - (68527-25-3)	Not Available	Not Available	Not Available
2,2'-Methylenebis(4-methyl-6-tert-butylphenol) - (119-47-1)	Not Available	Not Available	Not Available

### 12.2. Persistence and degradability

There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

### 12.6. Other adverse effects

No data available.

## Section 13. Disposal considerations

### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

## Section 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
<b>14.1. UN number</b>	UN1993	UN1993	UN1993

<b>14.2. UN proper shipping name</b>	UN1993, Flammable liquids, n.o.s., (Hexane), 3, III	Flammable liquids, n.o.s., (Hexane)	Flammable liquids, n.o.s., (Hexane)
<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class: 3</b>	<b>IMDG: 3</b>	<b>Air Class: 3</b>
<b>14.4. Packing group</b>	III	III	III
<b>14.5. Environmental hazards</b>			
<b>IMDG</b>	Marine Pollutant: ; ( Hexane )		
<b>14.6. Special precautions for user</b>			
	Not Applicable		

## Section 15. Regulatory information

**Regulatory Overview** The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

**Toxic Substance Control Act ( TSCA)** All components of this material are either listed or exempt from listing on the TSCA Inventory.

**EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**EPCRA 313 Toxic Chemicals:**

Hexane

**Proposition 65 - Carcinogens (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Male Repro Toxins (>0.0%):**

Hexane

**Proposition 65 Label Warning:**



WARNING: This product can expose you to chemicals including [Hexane], which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## Section 16. Other information

**Revision Date** 06/28/2022

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein.

We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H360 May damage fertility or the unborn child.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

**SDS Revision History**

<b>Version 1.1</b>	<b>Initial SDS issued</b>	<b>3/16/2015</b>
<b>Version 1.2</b>	<b>Change to Emergency Tele. Number</b>	<b>6/17/2015</b>
<b>Version 1.3</b>	<b>Updated Emergency Tele. Number and Prop 65 Listing</b>	<b>11/07/2018</b>
<b>Version 2.1</b>	<b>Document revised for formula change</b>	<b>6/28/2022</b>

ALL INFORMATION IS BASED UPON DATA FROM MFG'S AND/OR TECHNICAL SOURCE, & IS BELIEVED TO BE ACCURATE. CONDITIONS OF USE ARE BEYOND OUR CONTROL & THEREFORE USERS ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN CONDITIONS TO DETERMINE SUITABILITY FOR THEIR PURPOSE, & THEY ASSUME ALL RISKS OF USE, HANDLING, & DISPOSAL, OR FROM USE OF INFORMATION CONTAINED HEREIN. THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT RELATE TO ITS USE IN COMBINATION WITH OTHER MATERIAL OR IN ANY OTHER PROCESS.

End of Document