

Safety Data Sheet
Staseal 5000B Gray



SDS Revision: Version 1.3
SDS Revision Date: 12/12/2018

1. Identification

1.1. Product identifier

Product Identity Staseal 5000B Gray
Alternate Names Staseal 5000B Gray

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name STABOND CORPORATION
1722 W. 139th Street, GARDENA CA. 90249
Customer Service: STABOND CORPORATION (310) 380-6168 Mon. to Fri. 07:00 – 15:30 PT
Emergency Contact: CHEMTREC (800) 424-9300 24-hour

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Skin Sens. 1;H317 May cause an allergic skin reaction.
Resp. Sens. 1;H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carc. 2;H351 Suspected of causing cancer.
STOT RE 2;H373 May cause damage to organs through prolonged or repeated exposure. Specific Target Organs: (Not Available)

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H317 May cause an allergic skin reaction.
H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

[Prevention]:

- P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
 P262 Do not get in eyes, on skin, or on clothing.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves / eye protection / face protection.
 P285 In case of inadequate ventilation wear respiratory protection.

[Response]:

- P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.
 P302+352 IF ON SKIN: Wash with plenty of soap and water.
 P304+341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P308+313 IF exposed or concerned: Get medical advice / attention.
 P314 Get Medical advice / attention if you feel unwell.
 P321 Specific treatment (see information on this label).
 P331 Do NOT induce vomiting.
 P333+313 If skin irritation or a rash occurs: Get medical advice / attention.
 P342+311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor / physician.
 P363 Wash contaminated clothing before reuse.

[Storage]:

- P405 Store locked up.

[Disposal]:

- P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|--|----------|---|--------|
| Oxirane,methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatob CAS Number: 0059675-67-1 | 25 - 50 | Skin Sens. 1;H317 Resp. Sens. 1;H334 | [1] |
| Calcium carbonate CAS Number: 0001317-65-3 | 25 - 50 | Not Classified | [1][2] |
| 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich CAS Number: 0068515-49-1 | 10 - 25 | Skin Irrit. 2;H315 Eye Irrit. 2;H319 | [1] |
| TALC (Mg3H2(SiO3)4) CAS Number: 0014807-96-6 | 1.0 - 10 | Not Classified | [1][2] |
| Amorphous silica, hydrophobic CAS Number: 0067762-90-7 | 1.0 - 10 | Not Classified | [1] |
| Solvent naphtha (petroleum), light aromatic CAS Number: 0064742-95-6 | 1.0 - 10 | Asp. Tox. 1;H304 | [1] |
| Diphenylmethanediisocyanate CAS Number: 0000101-68-8 | 1.0 - 10 | Carc. 2;H351 Acute tox. 4;H332 STOT RE 2;H373 | [1][2] |

| | | |
|--|--|--|
| | Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315 Resp. Sens. 1;H334 Skin Sens. 1;H317 | |
|--|--|--|

[1] Substance classified with a health or environmental hazard.
 [2] Substance with a workplace exposure limit.
 [3] PBT-substance or vPvB-substance.
 *The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

- General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
- Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Overview** INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:
 Vapor and aerosols can irritate eyes, nose and respiratory passages. Severe overexposure can cause fluid buildup in lungs. MDI vapor can cause respiratory sensitization with asthma-like symptoms.
- SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:
 SKIN-skin sensitization and irritation may develop after repeated and/or prolonged contact with human skin.
 EYES-Contact will irritate human eyes.
- SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:
 Skin contact may play a role in respiratory sensitization. Gloves should be worn at all times when working with this product.
- INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:
 Irritation of the mouth, pharynx, esophagus and stomach can develop following ingestion. Aspiration hazard – may enter lungs during swallowing or vomiting and cause lung damage. May cause signs of CNS depression such as dizziness, drowsiness etc.
- HEALTH HAZARDS (ACUTE AND CHRONIC):
 Eye: May cause irritation with tearing.
 Skin: May cause skin irritation, temporary stain & allergic sensitivity.
 Ingestion: May cause irritation and corrosion on the mouth and stomach tissue.
 Inhalation: May cause irritation to upper respiratory tract and lungs, breathlessness, cough, respiratory sensitization.

CARCINOGENICITY: NTP? NO, IARC MONOGRAPHS? NO, OSHA REGULATED?
NO

This product contains chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
May aggravate existing lung and skin problems.

See section 2 for further details.

Inhalation

May cause allergy or asthma symptoms of breathing difficulties if inhaled.

Skin

May cause an allergic skin reaction.

5. Fire-fighting measures

5.1. Extinguishing media

Dry chemical, foam, carbon dioxide and water fog.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Isocyanate vapor and mist, CO₂, CO, NO, trace of hydrogen cyanide.

Avoid breathing dust / fume / gas / mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

5.3. Advice for fire-fighters

Down-wind personnel must be evacuated. Do not reseal contaminated containers as pressure build-up may rupture them.

Water contamination will produce Carbon dioxide. If exposed to intense heat or fire, cool with gross amounts of water.

Caution. Combustible. Do not enter confined spaces without full bunker gear. Firefighters must wear positive pressure self-contained breathing apparatus and full protective clothing to protect against isocyanate vapors.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Major: Evacuate and ventilate spill area. Prevent entry into water system. Wear full protective equipment.

Minor: Absorb with inert absorbent material.

Eliminate ignition sources. Soak up with noncombustible absorbent material. Remove absorbent material for proper disposal.

7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used.

Examination of lung function should be carried out on a regular basis on persons applying this preparation.

Incompatible materials: Water, acid, base, alcohols, metal compounds, surface active materials.

Store indoors at 50-90 deg F. in original, unopened containers. Protect from atmospheric moisture. Replace outage with inert dry gas as nitrogen.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection**8.1. Control parameters****Exposure**

| CAS No. | Ingredient | Source | Value |
|--------------|---|----------|--|
| 0000101-68-8 | Diphenylmethanediisocyanate | OSHA | C 0.2 mg/m3 (0.02 ppm) |
| | | ACGIH | TWA: 0.005 ppm Ceiling: 0.01 ppm Skin, S |
| | | NIOSH | TWA 0.05 mg/m3 (0.005 ppm) C 0.2 mg/m3 (0.020 ppm) [10-minute] |
| | | Supplier | No Established Limit |
| 0001317-65-3 | Calcium carbonate | OSHA | TWA 15 mg/m3 (total) TWA 5 mg/m3 (resp) |
| | | ACGIH | TWA: 10 mg/m3 Ceiling: 20 mg/m3 |
| | | NIOSH | TWA 10 mg/m3 (total) TWA 5 mg/m3 (resp) |
| | | Supplier | No Established Limit |
| 0014807-96-6 | TALC (Mg ₃ H ₂ (SiO ₃) ₄) | OSHA | TWA 20 mppcf |
| | | ACGIH | Containing asbestos fibres TWA: 0.1 f/cc (K) A1, 1 Containing no asbestos fibres TWA: 2 mg/m3 (E) (respirable) |
| | | NIOSH | TWA 2 mg/m3 (resp) |
| | | Supplier | No Established Limit |
| 0059675-67-1 | Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatob | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| 0064742-95-6 | Solvent naphtha (petroleum), light aromatic | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| 0067762-90-7 | Amorphous silica, hydrophobic | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |

| | | | |
|--------------|--|----------|----------------------|
| | | Supplier | No Established Limit |
| 0068515-49-1 | 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|--|--------|---|
| 0000101-68-8 | Diphenylmethanediisocyanate | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0001317-65-3 | Calcium carbonate | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0014807-96-6 | TALC (Mg3H2(SiO3)4) | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0059675-67-1 | Oxirane,methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatob | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0064742-95-6 | Solvent naphtha (petroleum), light aromatic | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0067762-90-7 | Amorphous silica, hydrophobic | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0068515-49-1 | 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

8.2. Exposure controls

Respiratory

Atmospheric levels should be maintained below the exposure guideline. Use an approved, full-face, supplied air respirator or a NIOSH approved positive pressure, self-contained breathing apparatus if these levels are exceeded.

Eyes

Use safety glasses with side shields or chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

Skin

Selection of specific items such as gloves, boots, apron, or full-body suit will depend on operation. Use Neoprene, vinyl or nitrile rubber gloves.

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices

Remove contaminated clothing. Wash skin and launder clothing before use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

| | |
|--|--|
| Appearance | High Viscosity Gray Paste |
| Odor | Mild Solvent |
| Odor threshold | Not Measured |
| pH | Not Measured |
| Melting point / freezing point | Not Measured |
| Initial boiling point and boiling range | 320-350 F |
| Flash Point | 141F |
| Evaporation rate (Ether = 1) | Slower than Ether |
| Flammability (solid, gas) | Not Applicable |
| Upper/lower flammability or explosive limits | Lower Explosive Limit: 1.0% Upper Explosive Limit: 7.0% |
| Vapor pressure (Pa) | Not Measured |
| Vapor Density | Heavier than air |
| Specific Gravity | 1.3 |
| Solubility in Water | Nil |
| Partition coefficient n-octanol/water (Log Kow) | Not Measured |
| Auto-ignition temperature | Not Measured |
| Decomposition temperature | Not Measured |
| Viscosity (cSt) | Not Measured |
| Coating V.O.C. | 0.41 lb/gl (49 grams/liter) |
| Material V.O.C. | 0.41 lb/gl (49 grams/liter) |
| Solubility in Water | Nil, reacts with water |

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization: MAY OCCUR

In presence of strong bases, water or temp. over 160° C. Water contamination gives off CO₂, & may rupture containers.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Elevated temperatures, or contamination by incompatible materials.

10.5. Incompatible materials

Water, acid, base, alcohols, metal compounds, surface active materials.

10.6. Hazardous decomposition productsIsocyanate vapor and mist, CO₂, CO, NO, trace of hydrogen cyanide.**11. Toxicological information****Acute toxicity**

Based upon animal testing, the C9 aromatic hydrocarbon components (trimethylbenzenes and ethylmethylbenzenes) are presumed to cause fetal toxicity and/or decreased fetal and newborn weights if overexposure occurs during the early gestation period.

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LD50, mg/L/4hr | Inhalation Dust/Mist LD50, mg/L/4hr | Inhalation Gas LD50, ppm |
|---|------------------------------|--------------------------------|---------------------------------|-------------------------------------|--------------------------|
| Oxirane,methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatob - (59675-67-1) | No data available | No data available | No data available | No data available | No data available |
| Calcium carbonate - (1317-65-3) | No data available | No data available | No data available | No data available | No data available |
| 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich - (68515-49-1) | No data available | No data available | No data available | No data available | No data available |
| TALC (Mg3H2(SiO3)4) - (14807-96-6) | No data available | No data available | No data available | No data available | No data available |
| Amorphous silica, hydrophobic - (67762-90-7) | 1,000.00, Rat - Category: 4 | 2,000.00, Rat - Category: 4 | No data available | No data available | No data available |
| Solvent naphtha (petroleum), light aromatic - (64742-95-6) | 6,800.00, Rat - Category: NA | 3,400.00, Rabbit - Category: 5 | No data available | No data available | No data available |
| Diphenylmethanediisocyanate - (101-68-8) | 4,700.00, Rat - Category: 5 | No data available | No data available | No data available | No data available |

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

| Classification | Category | Hazard Description |
|-------------------------------|----------|--|
| Acute toxicity (oral) | --- | Not Applicable |
| Acute toxicity (dermal) | --- | Not Applicable |
| Acute toxicity (inhalation) | --- | Not Applicable |
| Skin corrosion/irritation | --- | Not Applicable |
| Serious eye damage/irritation | --- | Not Applicable |
| Respiratory sensitization | 1 | May cause allergy or asthma symptoms of breathing difficulties if inhaled. |
| Skin sensitization | 1 | May cause an allergic skin reaction. |
| Germ cell mutagenicity | --- | Not Applicable |
| Carcinogenicity | 2 | Suspected of causing cancer. |
| Reproductive toxicity | --- | Not Applicable |
| STOT-single exposure | --- | Not Applicable |

| | | |
|------------------------|-----|--|
| STOT-repeated exposure | 2 | May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | --- | Not Applicable |

12. Ecological information

12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/l | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l |
|---|---------------------------|----------------------------|--|
| Oxirane,methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatob - (59675-67-1) | Not Available | Not Available | Not Available |
| Calcium carbonate - (1317-65-3) | Not Available | Not Available | Not Available |
| 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich - (68515-49-1) | Not Available | Not Available | Not Available |
| TALC (Mg3H2(SiO3)4) - (14807-96-6) | Not Available | Not Available | Not Available |
| Amorphous silica, hydrophobic - (67762-90-7) | Not Available | Not Available | Not Available |
| Solvent naphtha (petroleum), light aromatic - (64742-95-6) | 9.22, Oncorhynchus mykiss | 6.14, Daphnia magna | 19.00 (72 hr), Selenastrum capricornutum |
| Diphenylmethanediisocyanate - (101-68-8) | Not Available | 129.70, Daphnia magna | Not Available |

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

| | DOT (Domestic Surface Transportation) | IMO / IMDG (Ocean Transportation) | ICAO/IATA |
|---|--|---|----------------------------------|
| 14.1. UN number | Not Applicable | Not Regulated | Not Regulated |
| 14.2. UN proper shipping name | Not Regulated | Not Regulated | Not Regulated |
| 14.3. Transport hazard class(es) | DOT Hazard Class: Not Applicable DOT Label: --- | IMDG: Not Applicable Sub Class: Not Applicable | Air Class: Not Applicable |
| 14.4. Packing group | Not Applicable | Not Applicable | Not Applicable |
| 14.5. Environmental hazards | | | |
| IMDG | Marine Pollutant: No | | |
| 14.6. Special precautions for user | | | |
| | No further information | | |

15. Regulatory information

| | |
|--|---|
| Regulatory Overview | The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. |
| Toxic Substance Control Act (TSCA) | All components of this material are either listed or exempt from listing on the TSCA Inventory. |
| WHMIS Classification | D2A |
| US EPA Tier II Hazards | Fire: No Sudden Release of Pressure: No Reactive: No Immediate (Acute): Yes Delayed (Chronic): Yes |
| EPCRA 311/312 Chemicals and RQs (lbs): | Diphenylmethanediisocyanate (5,000.00) |
| EPCRA 302 Extremely Hazardous: | To the best of our knowledge, there are no chemicals at levels which require reporting under this statute. |
| EPCRA 313 Toxic Chemicals: | Diphenylmethanediisocyanate |
| Proposition 65 - Carcinogens (>0.0%): | Carbon Black TALC (Mg ₃ H ₂ (SiO ₃) ₄) |
| Proposition 65 - Developmental Toxins (>0.0%): | Diisodecyl phthalate Methanol |
| Proposition 65 - Female Repro Toxins (>0.0%): | To the best of our knowledge, there are no chemicals at levels which require reporting under this statute. |
| Proposition 65 - Male Repro Toxins (>0.0%): | To the best of our knowledge, there are no chemicals at levels which require reporting under this statute. |
| New Jersey RTK Substances (>1%): | |

Diphenylmethanediisocyanate
Calcium carbonate
TALC (Mg₃H₂(SiO₃)₄)

Pennsylvania RTK Substances (>1%):

Diphenylmethanediisocyanate
Calcium carbonate
TALC (Mg₃H₂(SiO₃)₄)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

SDS Revision History

| | | |
|--------------------|---|-------------------|
| Version 1.1 | Initial SDS issued | 5/12/2015 |
| Version 1.2 | Section 1.3 Change to Emergency Tele. Number | 6/17/2015 |
| Version 1.3 | Section 1.3 Update to Emergency Tele. Number, Section 15 Removed Toluene and Ethyl Benzene from Prop 65 list | 12/12/2018 |

ALL INFORMATION IS BASED UPON DATA FROM MFG'S AND/OR TECHNICAL SOURCE, & IS BELIEVED TO BE ACCURATE. CONDITIONS OF USE ARE BEYOND OUR CONTROL & THEREFORE USERS ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN CONDITIONS TO DETERMINE SUITABILITY FOR THEIR PURPOSE, & THEY ASSUME ALL RISKS OF USE, HANDLING, & DISPOSAL, OR FROM USE OF INFORMATION CONTAINED HEREIN. THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT RELATE TO ITS USE IN COMBINATION WITH OTHER MATERIAL OR IN ANY OTHER PROCESS.

End of Document